
Designed In USA.

HEAVY DUTY SYSTEMS
DISPLAY EQUIPMENT



PERFORMANCE.
DURABILITY.
VALUE.

HDS
HEAVY DUTY SYSTEMS

www.heavydutysystems.com

sales@heavydutysystems.com

34” Countertop Refrigerated Display Case



Air duct outside the glass to remove condensation water



HDSRCTD-34

8.88 Digital Controller

LED Lights


STANDARD FEATURES

- Brilliant Internal LED illumination on top
- Digital temperature controller and display
- Adjustable chrome plated shelves
- 4 sides double glass
- Front Curved glass
- Sliding doors
- Maintenance free condenser
- Ventilated cooling system
- Automatic defrost
- Stainless Steel Interior and Exterior Base
- Air duct outside the glass to remove condensation water

PERFORMANCE. DURABILITY. VALUE.

Designed In USA.

34” Countertop Refrigerated Display Case



MODEL	HDSRCTD-34
Capacity-Cu.Ft.	5.7Cu.Ft.
Temperature range	0-12°C (32-53.6 °F)
Voltage/Hertz/Phase	110-120V~/60Hz/1
Rated Input Power	330W/3A
Horsepower	1/3HP
Refrigerant	R290
N.W.	66kg(145.5lbs)
G.W.	69.5kg(153.2lbs)
Overall Dimension	880×568×686mm
Overall Dimension	34.6×22.4×27.0inch
Package Dimmension	951×627×735mm
Package Dimmension	37.4×24.7×28.9inch
Voltage 220/50/1 Available	

34” Countertop Heated Display Case



LED Lights


Temperature Conteroller

HDSHCTD-34

STANDARD FEATURES

- Brilliant Internal LED illumination on top
- Stainless Steel Interior and Exterior
- Adjustable temperature controller
- Temperature display
- Adjustable chrome plated shelves
- Front Curved glass
- Sliding doors

34” Countertop Heated Display Case



MODEL	HDSHCTD-34
Capacity-Cu.Ft.	5.7Cu.Ft.
Temperature range	30-90°C (86-194 °F)
Voltage/Hertz/Phase	110-120V~/60Hz/1
Rated Input Power	1500W/13.1A
N.W.	43kg(94.8lbs)
G.W.	46kg(101.4lbs)
Overall Dimension	856×568×686mm
Overall Dimension	33.7×22.4×27.0inch
Package Dimmension	928×627×731mm
Package Dimmension	36.5×24.7×28.8inch
Voltage 220/50/1 Available	

Heater Proofer



HDSPW-11 / HDSPW-11-I



HDSPW-34 / HDSPW-34-I

STANDARD FEATURES


- Temperature display
- Mechanical temperature control
- Mechanical humidity control
- Two heating methods — by water or by air
- Ventilated heating system
- 4 casters, 2 with brakes
- Aluminum Alloy Housing

PERFORMANCE. DURABILITY. VALUE.


Designed In USA.

Heater Proofer


HDSPW-34




HDSPW-34-I
Insulated



HDSPW-11



HDSPW-11-I
Insulated



MODEL	HDSPW-11	HDSPW-11-I	HDSPW-34	HDSPW-34-I
Sheet pan capacity (18” x 26”)	11	11	34	34
Temperature range	30–75°C (86–167°F)	30–75°C (86–167°F)	30–75°C (86–167°F)	30–75°C (86–167°F)
Capacity	159 L	159 L	420 L	420 L
Rated Input Power	1800 W	1800 W	1800 W	1800 W
Voltage/Hertz/Phase	110–120V/60Hz	110–120V/60Hz	110–120V/60Hz	110–120V/60Hz
N.W.	37 kg	49 kg	50 kg	69 kg
G.W.	46 kg	58 kg	60 kg	79 kg
Product dimensions (mm)	536 x 862 x 830 mm	536 x 879 x 830 mm	536 x 862 x 1715 mm	536 x 879 x 1715 mm
Package dimensions (mm)	663 x 996 x 855 mm	663 x 996 x 855 mm	663 x 996 x 1740 mm	663 x 996 x 1740 mm

Voltage 220/50/1 Available


17” Countertop Refrigerated Display




HDSRCTM-17

STANDARD FEATURES

- Brilliant Internal LED illumination on sides
- Digital temperature controller and display
- Front curved glass door
- 4 sides double glass
- Maintenance free condenser
- Ventilated cooling system
- Automatic defrost



17” Countertop Refrigerated Display



MODEL	HDSRCTM-17
Capacity-Cu.Ft.	3.4Cu.Ft.
Temperature range	0-12°C (32-53.6 °F)
Voltage/Hertz/Phase	110-120V~/60Hz/1
Rated Input Power	190W/1.7A
Horsepower	1/6HP
Refrigerant	R290
N.W.	38.5kg(84.9lbs)
G.W.	41kg(90.4lbs)
Overall Dimension	425×404×1080mm
Overall Dimension	16.7×15.9×42.5inch
Package Dimmension	480×450×1135mm
Package Dimmension	18.9×17.7×44.7inch
Colour	White/Black/Silver

Voltage 220/50/1 Available


20” Floor Refrigerated Display



HDSRFM-20

STANDARD FEATURES


- Brilliant Internal LED illumination on sides
- Digital temperature controller and display
- Adjustable PVC coated shelves
- Front curved glass door
- 4 sides double glass
- Base Feet
- Ventilated cooling system
- Automatic defrost



PERFORMANCE. DURABILITY. VALUE.

Designed In USA.

20” Floor Refrigerated Display



MODEL	HDSRFM-20
Capacity-Cu.Ft.	9.5Cu.Ft.
Temperature range	0-12°C (32-53.6 °F)
Voltage/Hertz/Phase	110-120V~/60Hz/1
Rated Input Power	380W/3.4A
Horsepower	1/3HP
Refrigerant	R290
N.W.	89kg(196.2lbs)
G.W.	94.1kg(207.5lbs)
Overall Dimension	515×485×1895mm
Overall Dimension	20.3×19.1×74.6inch
Package Dimmension	580×540×1960mm
Package Dimmension	22.8×21.3×77.2inch
Colour	White/Black/Silver

Voltage 220/50/1 Available


20” Rotating Refrigerated Cake Display



HDSCRCD-4


STANDARD FEATURES

- Brilliant Internal LED illumination on 2 sides
- Digital temperature controller and display
- Rotational chrome plated shelves
- Round double glass
- Ventilated cooling system
- Automatic defrost



Decrease condensation

20” Rotating Refrigerated Cake Display



MODEL	HDSCRCD-4
Capacity-Cu.Ft.	2.6Cu.Ft.
Temperature range	2-12°C (35.6-53.6 °F)
Voltage/Hertz/Phase	110-120V~/60Hz/1
Rated Input Power	170W/1.95A
Horsepower	1/6HP
Refrigerant	R290
N.W.	45kg(99.2lbs)
G.W.	47.5kg(104.7lbs)
Overall Dimension	504×504×1060mm
Overall Dimension	19.8×19.8×41.7inch
Package Dimmension	525×525×1100mm
Package Dimmension	20.7×20.7×43.3inch
Voltage 220/50/1 Available	

Refrigerated Air Curtain Merchandiser



HDSRACM-36



HDSRACM-48

STANDARD FEATURES

- Brilliant Internal LED lighting at 2 front sides
- Digital temperature controller and display
- 4 Castors with 2 brakes
- Double tempered glass
- With night curtain
- Ventilated cooling system
- Automatic de frost
- Filter mesh in front of the base
- Adjustable shelves
- White Coated Galvanized Steel Interior with Stainless Steel Exterior
- Condensation water evaporated automatically
- Condensator at back side, free maintenance


OPTIONS

- Sliding doors

PERFORMANCE. DURABILITY. VALUE.

Designed In USA.

Refrigerated Air Curtain Merchandiser



MODEL	HDSRACM-36	HDSRACM-48
Capacity-Cu.Ft.	11.3Cu.Ft.	15.0Cu.Ft.
Temperature range	2-10°C (35.6-50 °F)	2-10°C (35.6-50 °F)
Voltage/Hertz/Phase	110-120V~/60Hz/1	110-120V~/60Hz/1
Rated Input Power	1500W/14.5A	1200W/13A
Horsepower	3/4HP	3/4HP
Refrigerant	R290	R290
N.W.	130.5kg(287.7lbs)	168kg(370.4lbs)
G.W.	153kg(337.3lbs)	184kg(405.7lbs)
Overall Dimension	918×792×1459mm	1204×811×1459mm
Overall Dimension	36.1×31.2×57.4inch	47.4×31.9×57.4inch
Package Dimmension	990×880×1600mm	1270×880×1610mm
Package Dimmension	39.0×34.6×63.0inch	50.0×34.6×63.4inch
	Voltage 220/50/1 Available	

Refrigerated Self-Serve Merchandiser (2–10°C)



HDSRSSM-2057



HDSRSSM-2069



HDSRSSM-4050

STANDARD FEATURES


- LED light
- Digital control
- Adjustable shelves
- 4 castors, 2 with brakes
- Stainless steel construction




PERFORMANCE. DURABILITY. VALUE.

Designed In USA.


Refrigerated Self-Serve Merchandiser (2–10°C)



HDSRSSM-2057



HDSRSSM-2069



HDSRSSM-4050

MODEL	HDSRSSM-2057	HDSRSSM-2069	HDSRSSM-4050
Capacity-Gross(L)	180 L	220 L	200 L
Temperature range(°C)	2-10	2-10	2-10
Rated Input Power(W)	1340/1300	1340/1300	1340/1300
Refrigerant	R404a/R290	R404a/R290	R404a/R290
Climate class	6	6	6
Overall Dimension (mm)	494 x 674 x 1450	494 x 674 x 1742	1000 x 635 x 1250
Type	Refrigerated	Refrigerated	Refrigerated

Voltage 220/50/1 Available

Heated Self-Serve Merchandiser (30–80°C)



HDSHSSM-2057



HDSHSSM-2069



HDSHSSM-4050

STANDARD FEATURES

- Stainless Steel Interior and Exterior
- Brilliant Internal LED lighting each shelf and bottom
- 2 adjustable glass shelves
- Double tempered glass
- 4 Castors with 2 brakes




PERFORMANCE. DURABILITY. VALUE.


Designed In USA.

DISPLAY


Heated Self-Serve Merchandiser (30–80°C)



HDSHSSM-2057



HDSHSSM-2069



HDSHSSM-4050

MODEL	HDSHSSM-2057	HDSHSSM-2069	HDSHSSM-4050
Capacity-Gross	180 L	220 L	7 Cu.Ft.
Temperature range(°C)	30-80°C (86-176 °F)	30-80°C (86-176 °F)	30-80°C (86-176 °F)
Rated Input Power(W)	2000	2000	2100
Overall Dimmension (mm)	494 x 600 x 1450	494 x 600 x 1742	1000 × 592 × 1253
Package Dimmension	-	-	1050 × 680 × 1400 mm
N.W.	-	-	104.5 kg (230.4 lbs)
G.W.	-	-	140 kg (308.6 lbs)
Type	Heated	Heated	Heated

Voltage 220/50/1 Available

Curved Glass Refrigerated Display Case



HDSCRBC-36



HDSCRBC-48



HDSCRBC-60

STANDARD FEATURES


- Stainless Steel Interior and Exterior
- Brilliant Internal LED lighting each shelf and bottom
- 2 adjustable glass shelves
- Digital temperature control and display
- Double tempered glass
- 4 Castors with 2 brakes
- Ventilated cooling system
- Automatic Defrost




PERFORMANCE. DURABILITY. VALUE.

Designed In USA.


Curved Glass Refrigerated Display Case



HDSCRBC-36



HDSCRBC-48



HDSCRBC-60

MODEL	HDSCRBC-36	HDSCRBC-48	HDSCRBC-60
Capacity-Cu.Ft.	10.4Cu.Ft.	14.1Cu.Ft.	17.6Cu.Ft.
Temperature range	0-12°C (32-53.6 °F)	0-12°C (32-53.6 °F)	0-12°C (32-53.6 °F)
Voltage/Hertz/Phase	110-120V~/60Hz/1	110-120V~/60Hz/1	110-120V~/60Hz/1
Rated Input Power	390W/3.7A	400W/3.7A	420W/4.0A
Horsepower	1/2HP	1/2HP	1/2HP
Refrigerant	R290	R290	R290
N.W.	135kg(297.6lbs)	155kg(341.7lbs)	182kg(401.2lbs)
G.W.	154kg(339.5lbs)	188kg(414.5lbs)	235kg(518lbs)
Overall Dimension	915×675×1220mm	1215×675×1220mm	1515×675×1220mm
Overall Dimension	36.0×26.6×48.0inch	47.8×26.6×48.0inch	59.6×26.6×48.0inch
Package Dimmension	1025×765×1280mm	1325×765×1280mm	1600×743×1270mm
Package Dimmension	40.4×30.1×50.4inch	52.2×30.1×50.4inch	63.0×29.3×50.0inch
Voltage 220/50/1 Available			

Curved Glass Non-Refrigerated Display Case



HDSCDBC-36



HDSCDBC-48




HDSCDBC-60

STANDARD FEATURES


- Stainless Steel Interior and Exterior
- Brilliant Internal LED lighting each shelf and bottom
- 2 adjustable glass shelves
- Double tempered glass
- 4 Castors with 2 brakes




Curved Glass Non-Refrigerated Display Case



HDSCDBC-36



HDSCDBC-48



HDSCDBC-60

MODEL	HDSCDBC-36	HDSCDBC-48	HDSCDBC-60
Capacity-Cu.Ft.	10.4Cu.Ft.	14.1Cu.Ft.	17.6Cu.Ft.
Voltage/Hertz/Phase	110-120V~/60Hz/1	110-120V~/60Hz/1	110-120V~/60Hz/1
Rated Input Power	0.2A	0.3A	0.3A
N.W.	105kg(231.5lbs)	130kg(286.6lbs)	158kg(348.3lbs)
G.W.	124kg(273.4lbs)	163kg(359.4lbs)	211kg(465.2lbs)
Overall Dimension	915×675×1220mm	1215×675×1220mm	1515×675×1220mm
Overall Dimension	36.0×26.6×48.0inch	47.8×26.6×48.0inch	59.6×26.6×48.0inch
Package Dimmension	1025×765×1280mm	1325×765×1280mm	1600×743×1270mm
Package Dimmension	40.4×30.1×50.4inch	52.2×30.1×50.4inch	63.0×29.3×50.0inch

Voltage 220/50/1 Available

Curved Glass Heated



HDSCHBC-36



HDSCHBC-48



HDSCHBC-60

STANDARD FEATURES


- Circulating air heating for uniform temperature
- Internal LED lighting
- Swivel casters with brake
- Adjustable glass shelves
- Four-sided insulated glass




PERFORMANCE. DURABILITY. VALUE.

Designed In USA.


Curved Glass Heated



HDSCHBC-36



HDSCHBC-48



HDSCHBC-60

MODEL	HDSCHBC-36	HDSCHBC-48	HDSCHBC-60
Capacity	320 L	435 L	560 L
Voltage/Hertz	110–120V~/60Hz	220V~/60Hz	220V~/60Hz
Rated Input Power	1450 W	2700 W	2700 W
N.W.	88 kg	112 kg	138 kg
G.W.	122 kg	154 kg	191 kg
Temperature range	30–90°C (86–194°F)	30–90°C (86–194°F)	30–90°C (86–194°F)
Overall Dimension	900×680×1210 mm	1200×680×1210 mm	1500×680×1210 mm
Overall Dimension	35.43×26.77×47.24inch	47.24×26.77×47.24inch	59.06×26.77×47.64inch

Voltage 220/50/1 Available

Square Glass Refrigerated Display Case



HDSSRBC-36



HDSSRBC-48



HDSSRBC-60

STANDARD FEATURES


- Stainless Steel Interior and Exterior
- Brilliant Internal LED lighting each shelf and bottom
- 2 adjustable glass shelves
- Digital temperature control and display
- Double tempered glass
- 4 Castors with 2 brakes
- Ventilated cooling system
- Automatic Defrost




PERFORMANCE. DURABILITY. VALUE.

Designed In USA.


Square Glass Refrigerated Display Case



HDSSRBC-36



HDSSRBC-48



HDSSRBC-60

MODEL	HDSSRBC-36	HDSSRBC-48	HDSSRBC-60
Capacity-Cu.Ft.	10.4Cu.Ft.	14.1Cu.Ft.	18.0Cu.Ft.
Temperature range	0-12°C (32-53.6 °F)	0-12°C (32-53.6 °F)	0-12°C (32-53.6 °F)
Voltage/Hertz/Phase	110-120V~/60Hz/1	110-120V~/60Hz/1	110-120V~/60Hz/1
Rated Input Power	390W/3.7A	400W/3.7A	420W/4.0A
Horsepower	1/2HP	1/2HP	1/2HP
Refrigerant	R290	R290	R290
N.W.	135kg(297.6lbs)	155kg(341.7lbs)	182kg(401.2lbs)
G.W.	154kg(339.5lbs)	188kg(414.5lbs)	235kg(518lbs)
Overall Dimension	915×675×1210mm	1215×675×1210mm	1515×675×1210mm
Overall Dimension	36.0×26.6×47.6inch	47.8×26.6×47.6inch	59.6×26.6×47.6inch
Package Dimmension	1025×765×1280mm	1325×765×1280mm	1600×743×1270mm
Package Dimmension	40.4×30.1×50.4inch	52.2×30.1×50.4inch	63.0×29.3×50.0inch
Voltage 220/50/1 Available			

Square Glass Non-Refrigerated Display Case



HDSSDBC-36



HDSSDBC-48



HDSSDBC-60

STANDARD FEATURES


- Stainless Steel Interior and Exterior
- Brilliant Internal LED lighting each shelf and bottom
- 2 adjustable glass shelves
- Double tempered glass
- 4 Castors with 2 brakes




PERFORMANCE. DURABILITY. VALUE.

Designed In USA.


Square Glass Non-Refrigerated Display Case



HDSSDBC-36



HDSSDBC-48



HDSSDBC-60

MODEL	HDSSDBC-36	HDSSDBC-48	HDSSDBC-60
Capacity-Cu.Ft.	10.4Cu.Ft.	14.1Cu.Ft.	18.0Cu.Ft.
Voltage/Hertz/Phase	110-120V~/60Hz/1	110-120V~/60Hz/1	110-120V~/60Hz/1
Rated Input Power	0.2A	0.3A	0.3A
N.W.	106.5kg(234.8lbs)	133kg(293.2lbs)	160.5kg(353.8lbs)
G.W.	125.5kg(276.7lbs)	166kg(366.0lbs)	213.5kg(470.1lbs)
Overall Dimension	915×675×1210mm	1215×675×1210mm	1515×675×1210mm
Overall Dimension	36.0×26.6×47.6inch	47.8×26.6×47.6inch	59.6×26.6×47.6inch
Package Dimmension	1025×765×1280mm	1325×765×1280mm	1600×743×1270mm
Package Dimmension	40.4×30.1×50.4inch	52.2×30.1×50.4inch	63.0×29.3×50.0inch

Voltage 220/50/1 Available

Square Glass Heated



HDSSHBC-36



HDSSHBC-48



HDSSHBC-60

STANDARD FEATURES


- Circulating air heating for uniform temperature
- Internal LED lighting
- Swivel casters with brake
- Adjustable glass shelves
- Four-sided insulated glass




PERFORMANCE. DURABILITY. VALUE.

Designed In USA.


Square Glass Heated



HDSSHBC-36



HDSSHBC-48



HDSSHBC-60

MODEL	HDSSHBC-36	HDSSHBC-48	HDSSHBC-60
Capacity	330 L	445 L	560 L
Voltage/Hertz	110–120V~/60Hz	220V~/60Hz	220V~/60Hz
Rated Input Power	1450 W	2700 W	2700 W
Temperature range	30–90°C (86–194°F)	30–90°C (86–194°F)	30–90°C (86–194°F)
Overall Dimension	900×680×1200 mm	1200×680×1200 mm	1500×680×1200 mm
Overall Dimension	35.43×26.77×47.24inch	47.24×26.77×47.24in	59.06×26.77×47.64inch

Voltage 220/50/1 Available



PERFORMANCE. DURABILITY. VALUE.

sales@heavydutysystems.com

www.heavydutysystems.com